

Welcome! to our world

versatility

RM MS + RM RFB
MORE VALUE, MORE OPPORTUNITIES.



MS + RFB

RM MS + RM RFB – MESH SCREEN AND SWIVEL REFEEDING BELT

GENERAL INFORMATION

	RM MS95GO!	RM MS105GO!
Output	Up to 160 t/h depending on material	Up to 200 t/h depending on material
Feed material size	Edge length max. 70 mm	Edge length max. 70 mm
Screening range	0/4 to 0/70 mm	0/4 to 0/70 mm
Weight without refeeding belt	3 t	3.5 t
Weight with refeeding belt	3.9 t	4.6 t
Transport system/type	With/without machine	With/without machine
Deck data	1 deck split	1 deck split
Discharge height	2,500 mm	2,760 mm
Oversize belt width	500 mm	500 mm
Fines belt width	1,000 mm	1,200 mm
Mesh tensioning	Length tensioned	Length tensioned
Screen length	2 x 1,170 mm	2 x 1,520 mm
Screen width	1,100 mm	1,300 mm
Screen media	Mesh	Mesh

MOUNTED ON CRUSHER

Working position length	13,465 mm	14,590 mm
Working position width	2,700 mm	2,900 mm
Working position height	4,090 mm	4,160 mm
Transport length	13,465 mm	14,590 mm
Transport width	2,550 mm	2,810 mm
Transport height	3,050 mm	3,155 mm

WITHOUT MACHINE

Transport length MS + RFB	5,470 mm	6,000 mm
Transport width MS + RFB	2,550 mm	2,810 mm
Transport width MS	2,400 mm	2,500 mm
Transport height MS + RFB	1,600 mm	1,900 mm

	RM RFB7540GO!	RM RFB7550GO!
System	Hopper refeeding or swivel to stockpile	Hopper refeeding or swivel to stockpile
Length	7,580 mm	7,580 mm
Width	685 mm	785 mm
Height	570 mm	570 mm
Transport weight (Including assembly components)	906 kg	1,160 kg
Belt width	400 mm	500 mm
Belt type	Chevron	Chevron